

TRANCE X E+ 3



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
MANDO	RideControl Ergo 3, grip integrated
PANTALLA	RideControl GO, frame integrated LED displayANT+ Wireless display compatible
BATERÍA	EnergyPak Smart 625Wh, EnergyPak Plus range extender compatible
CUADRO	
TALLAS	S, M, L, XL
COLORES	Black Diamond
CUADRO	ALUXX SL-Grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH derailleur hanger, Giant EnergyPak Plus Range Extender Compatible
HORQUILLA	RockShox 35 Gold RL DebonAir, 150mm travel, 44mm offset, MotionControl™ rebound and lockout control, 15x110 Boost, Maxle Stealth, e-MTB optimized
AMORTIGUADOR	Rock Shox Deluxe R, 185x52.5mm Trunnion mount, custom tuned
COMPONENTES	
MANILLAR	Giant Contact 35 Trail, 35x780mm
PUÑOS	Giant Tactal Pro-E, single lock-on
POTENCIA	Giant Contact SL 35
TIJA DE SILLÍN	Giant Contact Switch, dropper, 30,9mm (S:125, M: 150, L/XL:170)
SILLÍN	Giant Romero Trail
PEDALES	Flat pedal
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore
DESVIADOR	MRP HD2 co-moulded chain guide
CAMBIO TRASERO	Shimano Deore 12-speed
FRENOS	Shimano BR-M420, 4-piston, hydraulic disc, 203mm
PALANCAS DE FRENOS	Shimano Deore BL-M4100, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CADENA	KMC e.12 Turbo, EcoProteq, e-bike optimized
JGO. PLATOS Y BIELAS	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S:160, M/L: 165, XL:170)
CAJA DE PEDALIER	-

RUEDAS	
LLANTAS	Giant AM 29", Tubeless ready, 30mm inner width
BUJES	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RADIOS	Sapim E-Lite [R] Race [F]
CUBIERTAS	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+ [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESORIOS	
LUCES	Optional:- Giant Recon series e-bike lights available and direct connectable

Precio: 4.899 €

GEOMETRÍA

CUADRO	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Longitud del tubo del sillín (mm)	400	425	450	475
Ángulo del tubo del sillín	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°
Longitud del tubo superior (mm) (mm)	577 575	610 605	637 635	667 665
Longitud del tubo de dirección (mm) (mm)	95	100	110	120
Ángulo del tubo de dirección	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Inclinación de la horquilla (mm)	44	44	44	44
Trail (mm) (mm)	117 122,4	117 122,4	117 122,4	117 122,4
Distancia entre ejes (mm) (mm)	1205 1206	1239 1237	1268 1269	1300 1301
Longitud de la vaina (mm) (mm)	473 473	473 473	473 473	473 473
Caída del eje de pedalier (mm) (mm)	30 20	30 20	30 20	30 20
Stack (mm) (mm)	606 601	611 605	621 614	630 624
Reach (mm) (mm)	439 447	457 462	482 489	510 517
Altura del suelo al tubo (mm) (mm)	783 789	775 784	763 770	775 782
Ancho del manillar (mm) (mm)	780	780	780	780
Longitud de la potencia (mm) (mm)	40	40	50	50
Longitud de las bielas (mm) (mm)	160	165	165	170
Tamaño de ruedas	29"	29"	29"	29"

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.